

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.10.2020

Version number 2

Revision: 16.10.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: VERNIS PLG

Article number: 00294

Registration number N.A

UFI: VY40-M06K-T00J-H4F7

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Water-based Paint / Varnish / Dyeing for industrial application

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

STILZ CHIMIE S.A.

B.P. 7

F-86530 cenon sur Vienne

Tel: +33 (0)5 49 20 08 50

Fax: +33 (0)5 49 21 44 37

mail: stilzchem@wanadoo.fr

Further information obtainable from:

Service FDS

E-mail: stilzchem@wanadoo.fr

1.4 Emergency telephone number:

M.Revel Tel.: +33 (0)5 49 20 08 50

(Du lundi au jeudi de 8h30 à 12h00 et de 14h00 à 17h00

le vendredi de 8h30 à 11h30)

Numéro ORFILA (INRS): + 33 (0)1 45 42 59 59

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.10.2020

Version number 2

Revision: 16.10.2020

Trade name: VERNIS PLG

(Contd. of page 1)

Hazard pictograms



Signal word Danger

Hazard-determining components of labelling:

butanone

Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240 Ground and bond container and receiving equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 78-93-3 EINECS: 201-159-0 Reg.nr.: 01-2119457290-43-xxxx	butanone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	25-75%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226	≥1-≤2.5%
CAS: 1333-86-4 EINECS: 215-609-9 Reg.nr.: 01-2119384822-32	carbon black substance with a Community workplace exposure limit	1-2.5%

(Contd. on page 3)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.10.2020

Version number 2

Revision: 16.10.2020

Trade name: VERNIS PLG

		(Contd. of page 2)
CAS: 108-10-1 EINECS: 203-550-1	4-methylpentan-2-one ⚠ Flam. Liq. 2, H225; ⚠ Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H335	1-2.5%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Immediately remove any clothing soiled by the product.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Immediately rinse with water.

After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters

Protective equipment: No special measures required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Prevent seepage into sewage system, workpits and cellars.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Prevent formation of aerosols.

Handling: Wear suitable gloves.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

(Contd. on page 4)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.10.2020

Version number 2

Revision: 16.10.2020

Trade name: VERNIS PLG

(Contd. of page 3)

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Store in a cool location.

Information about storage in one common storage facility: Not required.

Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

CAS: 78-93-3 butanone

WEL	Short-term value: 899 mg/m ³ , 300 ppm Long-term value: 600 mg/m ³ , 200 ppm Sk, BMGV
-----	---

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

WEL	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk
-----	--

CAS: 1333-86-4 carbon black

WEL	Short-term value: 7 mg/m ³ Long-term value: 3.5 mg/m ³
-----	---

CAS: 108-10-1 4-methylpentan-2-one

WEL	Short-term value: 416 mg/m ³ , 100 ppm Long-term value: 208 mg/m ³ , 50 ppm Sk, BMGV
-----	--

Ingredients with biological limit values:

CAS: 78-93-3 butanone

BMGV	70 µmol/L Medium: urine Sampling time: post shift Parameter: butan-2-one
------	---

CAS: 108-10-1 4-methylpentan-2-one

BMGV	20 µmol/L Medium: urine Sampling time: post shift Parameter: 4-methylpentan-2-one
------	--

Additional information: The lists valid during the making were used as basis.

(Contd. on page 5)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.10.2020

Version number 2

Revision: 16.10.2020

Trade name: VERNIS PLG

(Contd. of page 4)

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form:	Fluid
Colour:	Black
Odour:	Like aromatic solvents
Odour threshold:	Not determined.

pH-value: Not determined.

Change in condition

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	78-81 °C

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.10.2020

Version number 2

Revision: 16.10.2020

Trade name: VERNIS PLG

(Contd. of page 5)

Flash point:	< 0 °C
Flammability (solid, gas):	Not applicable.
Decomposition temperature:	Not determined.
Auto-ignition temperature:	404°C
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	1 Vol %
Upper:	11.5 Vol %
Vapour pressure at 20 °C:	105 hPa
Density at 20 °C:	0.87-0.9 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Solvent content:	
Organic solvents:	72.2-72.3 %
Solids content:	27.5-27.6 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions No dangerous reactions known.

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:		
CAS: 78-93-3 butanone		
Oral	LD50	3,300 mg/kg (rat)

(Contd. on page 7)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.10.2020

Version number 2

Revision: 16.10.2020

Trade name: VERNIS PLG

(Contd. of page 6)

Dermal	LD50	5,000 mg/kg (rbt)
CAS: 108-65-6 2-methoxy-1-methylethyl acetate		
Oral	LD50	8,532 mg/kg (rat)
Inhalative	LC50/4 h	35.7 mg/l (rat)
CAS: 108-10-1 4-methylpentan-2-one		
Oral	LD50	2,080 mg/kg (rat)
Dermal	LD50	16,000 mg/kg (rab)
Inhalative	LC50/4 h	8.3-16.6 mg/l (rat)

Primary irritant effect:

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Additional ecological information:

General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.10.2020

Version number 2

Revision: 16.10.2020

Trade name: VERNIS PLG

(Contd. of page 7)

SECTION 14: Transport information

14.1 UN-Number ADR, IMDG, IATA	UN1263
14.2 UN proper shipping name ADR IMDG, IATA	1263 PAINT RELATED MATERIAL, (vapour pressure at 50°C not more than 110 kPa) PAINT RELATED MATERIAL
14.3 Transport hazard class(es) ADR  Class Label	3 (F1) Flammable liquids. 3
IMDG, IATA  Class Label	3 Flammable liquids. 3
14.4 Packing group ADR, IMDG, IATA	II
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category	Warning: Flammable liquids. 33 F-E, <u>S</u> -E B
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml 2 D/E

(Contd. on page 9)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.10.2020

Version number 2

Revision: 16.10.2020

Trade name: VERNIS PLG

(Contd. of page 8)

IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL (VAPOUR PRESSURE AT 50°C NOT MORE THAN 110 KPA), 3, II

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

National regulations:

Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

Department issuing SDS:

Service Qualité

E-mail: contact@stilz-chimie.com

Contact: R. Revel : Tel.: +33(0)5 49 20 08 50

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.10.2020

Version number 2

Revision: 16.10.2020

Trade name: VERNIS PLG

(Contd. of page 9)

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - inhalation – Category 4

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3